

Characteristics when operating with the preferred fuel only:

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Heat output				Useful efficiency (NCV as received)			
Nominal heat output	P_{nom}	10,3	kW	Useful efficiency at nominal heat output	$\eta_{th,nom}$	92,2	%
Minimum heat output (indicative)	P_{min}	2,8	kW	Useful efficiency at minimum heat output (indicative)	$\eta_{th,min}$	92,2	%
Auxiliary electricity consumption				Type of heat output/room temperature control (select one)			
At nominal heat output	el_{max}	0,105	kW	single stage heat output, no room temperature control		no	
At minimum heat output	el_{min}	0,021	kW	two or more manual stages, no room temperature control		no	
In standby mode	el_{SB}	0,003	kW	with mechanic thermostat room temperature control		no	
Permanent pilot flame power requirement				with electronic room temperature control		no	
Pilot flame power requirement (if applicable)	P_{pilot}	n.p.	kW	with electronic room temperature control plus day timer		no	
				with electronic room temperature control plus week timer		no	
				Other control options (multiple selections possible)			
				room temperature control, with presence detector		no	
				room temperature control, with open window detection		no	
				with distance control option		no	

Contact details	Name and address of the manufacturer or its authorised representative
+39 0445 741310 +39 0445 741657 export@thermorossi.it www.thermorossi.com	THERMOROSSI S.p.A. Via Grumulo, 4 - 36011 Arsiero (VI) - IT

(*) PM = particulate matter, OGC = organic gaseous compounds, CO = carbon monoxide, NO_x = nitrogen oxides

(**) Only required if correction factors F(2) or F(3) are applied

Note:

F(2)	0
F(3)	0
Technical report ref.	2003277/03
Extended models	Slimquadro 11 Cristallo - Slimquadro 11 Maiolica

Approved by
Maurizio Lorenzon
Industry Division Manager


